

# DISPENSERS

# SUZZARABLU SIDE PRO/BASIC



**EN.** The dispensing group has been designed to be easily moved from an IBC tank to another.

We have installed a self priming diaphragm pump, without dynamic seal, in order to reduce the need of maintenance.

The group is provided with an accurate meter to display the quantity dispensed and with an automatic nozzle to make the filling operation easier.

**RU.** Конструкция узла подачи позволяет просто снять его с резервуара IBC и установить на другой резервуар. Установлен самозаливающийся мембранный насос без динамического уплотнения для уменьшения объема необходимого техобслуживания. Узел оснащен точным счетчиком литров для отображения поданного количества и автоматическим пистолетом, который упрощает перекачку.

**DE.** Die Abgabeeinheit ist so konzipiert, dass sie leicht von einem IBC-Behälter zum anderen versetzt werden kann. Zwecks minimaler Wartung wurde eine selbstansaugende Membranpumpe ohne dynamische Dichtung angebracht. Die Einheit verfügt über einen exakten Literzähler zur Anzeige der abgegebenen Menge und eine automatische Zapfpistole, die das Umfüllen erleichtert.

## PERFORMANCE

### SUZZARABLU BASIC

Stainless steel base.

Pump.

Manual nozzle.

Delivery hose 6 m.

Suction hose 1,5 m.

Hose tail and clamps.

### SUZZARABLU BASIC

Опорный лист из нержавеющей стали.

Электронасос.

Ручной пистолет.

Нагнетательная труба 6 м.

Всасывающая труба 1,5 м.

Штуцер и хомуты.

### SUZZARABLU BASIC

Rostfreie Grundplatte.

Elektropumpe.

Manuelle Zapfpistole.

Druckschlauch 6 m.

Saugschlauch 1,5 m.

Schlauchanschlussstück und Schellen.

### SUZZARABLU PRO

Stainless steel base with nozzle holder.

Heavy duty pump.

Meter K24.

Automatic stainless steel nozzle.

Delivery hose 6 m.

Suction hose 1,5 m.

Hose tail and clamps.

### SUZZARABLU PRO

Опорный лист из нержавеющей стали с держателем пистолета.

Электронасос.

Узел счетчика литров K24.

Автоматический пистолет из нержавеющей стали.

Нагнетательная труба 6 м.

Всасывающая труба 1,5 м.

Штуцер и хомуты.

### SUZZARABLU PRO

Rostfreie Grundplatte mit Zapfpistolenhalter.

Elektropumpe.

Literzähler K24.

Automatische Zapfpistole aus Edelstahl.

Druckschlauch 6 m.

Saugschlauch 1,5 m.

Schlauchanschlussstück und Schellen.



## PRODUCTS' RANGE WEIGHT AND PACKAGING

Code	Weight		mm	Packaging	
	kg	lbs		inch	pcs/box
F00201B1A	16	35,3	480x370x265	18,3x14,6x10,4	1
F00201C9A	16	35,3	480x370x265	18,3x14,6x10,4	1
F00201BAB	16	35,3	480x370x265	18,3x14,6x10,4	1
F00201A8A	12,6	27,8	480x370x265	18,3x14,6x10,4	1
F00201B2A	16	35,3	480x370x265	18,3x14,6x10,4	1
F00201E8A	16	35,3	480x370x265	18,3x14,6x10,4	1
F00201E7A	16	35,3	480x370x265	18,3x14,6x10,4	1
F00201A9A	12,6	27,8	480x370x265	18,3x14,6x10,4	1

Flow-rate

up to  
**32** l/min  
(up to 8,5 gpm)

Accuracy

+/-  
**1%**



**PIUSI**<sup>®</sup>

DISPENSERS



SUZZARABLUe BASIC



SUZZARABLUe PRO (K24+SB325 nozzle)



SUZZARABLUe EXTERNAL SUCTION

PUMPS

METERS

NOZZLE METERS



SUZZARABLUe BASIC 12V



SUZZARABLUe PRO (K24+A60 inox nozzle)



SUZZARABLUe TROLL  
(SIDE + TROLL Code R12068010  
+ DIP TUBE Code F15606000)

NOZZLE

SPECIAL EQUIPMENTS

INCLUDED

SEC connection



ON REQUEST

K24 meter



Automatic nozzle SB325 meter




Troll



Code R12068010

Dip tube



Code F15606000

FLUID MONITORING

ACCESSORIES

PRODUCTS' RANGE TECHNICAL DATA

Code	Description	Fluids		Flow-rate		Voltage			Meter mod.	Nozzle type	Suction	Hose lenght Ø 3/4"	On/Off switch
		type		l/min	gpm	AC V/Hz	DC Volt	Power Watt					
F00201B1A	SUZZARABLUe PRO K24 + Inox nozzle	U		32	8,5	230/50	400	1,95	YES	Aut.	SEC	6 m	YES
F00201C9A	SUZZARABLUe PRO K24+SB325	U		32	8,5	230/50	400	1,95	YES	SB325	SEC	6 m	YES
F00201BAB	SUZZARABLUe PRO K24+SB325+ ext. suction	U		32	8,5	230/50	400	1,95	YES	SB325	BOTTOM	6 m	YES
F00201A8A	SUZZARABLUe PRO 12V K24 + Inox nozzle	U		35	9,2	12	260	22	YES	Aut.	SEC	6 m	YES
F00201B2A	SUZZARABLUe BASIC	U		32	8,5	230/50	400	1,95	NO	Man.	SEC	6 m	YES
F00201E8A	SUZZARA BLUe BASIC + SB325	U		32	8,5	230/50	400	1,95	NO	SB325	SEC	6 m	YES
F00201E7A	SUZZARABLUe BASIC + SB325 + 8 mt hose	U		32	8,5	230/50	400	1,95	NO	SB325	SEC	8 m	YES
F00201A9A	SUZZARABLUe BASIC 12V	U		35	9,2	12	260	22	NO	Man.	SEC	6 m	YES

FILTERING